

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) Device for filling storage containers on dispensing appliances having a pump unit and a metering cylinder for each component, the storage containers being connected to the metering cylinders, ~~characterized in that~~ wherein the device comprises a filling station (30) for receiving the dispensing appliance that includes a coupling arrangement (4,5) between each storage container (2,3) and an associated coupling (6,7) of the filling station, each coupling arrangement comprising an appliance coupling part (28) and a station coupling part (29), and the coupling arrangements being arranged on the same axis and opposite each other between the outlets of the storage containers and the inlets of the metering units.
2. (Currently Amended) Device according to claim 1, ~~characterized in that~~ wherein the appliance coupling part (28) is arranged in an inlet nozzle (17) of the dispensing appliance and the station coupling part (29) in a guide (31) in the support (33) of the filling station (30).
3. (Currently Amended) Device according to claim 2, ~~characterized in that~~ wherein the station coupling part (29) comprises a coupling head (24) that is displaceable with respect to the guide (31) and a sealing cylinder (21) that receives an opening push rod (18) and is displaceable with respect to the coupling head and includes a centering portion (32) that is slidable over a centering sleeve (15) on the inlet nozzle (17) of the dispensing appliance.
4. (Currently Amended) Device according to ~~any one of claims 1 to 3~~ claim 1, ~~characterized in that~~ wherein the appliance coupling part (28) comprises a valve head (12) under the action of a first compression spring (14) and the opening push rod (18) in the station coupling part (29) is under the action of a second compression spring (20), the push rod shaft (19) of the opening push rod being secured in the coupling head and the latter being actuatable by an actuating member (9).

5. (Currently Amended) Device according to ~~any one of claims 1 to 4~~ claim 1, ~~characterized in that~~ wherein the coupling arrangement (4, 5) comprises sealing means (16; 22, 23) sealing the valve head (12) and the opening push rod (18) against the inlet nozzle (17).
6. (Currently Amended) Device according to claim 5, ~~characterized in that~~ wherein the opening push rod (18) is arranged in a sealing cylinder (21) that is disposed in the coupling head (24) and is sealed against the coupling head (24) by means of a joint (25).
7. (Currently Amended) Device according to ~~any one of claims 1 to 6~~ claim 1, ~~characterized in that~~ wherein the coupling head (24) comprises a joint (22) arranged in the sealing cylinder (21) that seals the sealing cylinder both against a conical portion of the opening push rod and against the inlet nozzle.
8. (Currently Amended) Device according to ~~any one of claims 1 to 7~~ claim 1, ~~characterized in that~~ wherein it comprises two coupling arrangements (4, 5) that are each actuatable by mechanical (8, 9) and/or electric and/or pneumatic and/or hydraulic actuating means.
9. (Currently Amended) Method ~~according to one of claims 1 to 8~~ for filling storage containers on a dispensing appliance with a device according to claim 1, ~~characterized in that~~ wherein the dispensing appliance is introduced in the opened filling station and by actuating the quick clamps, both the dispensing appliance is clamped and the valves in the appliance coupling part and in the station coupling part are opened, after which, by unlocking and actuating the quick clamps, the valves are closed and the dispensing appliance is released and may be removed.